


Odbočka Geberit PE 45°



Obrázek s příkladem



ÚČEL POUŽITÍ

- K odvodnění budov
- K odvodnění pozemků

VLASTNOSTI

- Odolný vůči UV

TECHNICKÉ ÚDAJE

Materiál

PE-HD

Pol. č.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
379.108.16.1	30	32	32	45	10.5	3.5	7	7	2	2	2
360.108.16.1	40 / 30	40	32	45	13.5	4.5	9	9	3	3.5	3.5
360.109.16.1	40	40	40	45	13.5	4.5	9	9	2.5	3	3
361.109.16.1	50 / 40	50	40	45	16.5	5.5	11	11	4	4.5	4.5
361.112.16.1	50	50	50	45	16.5	5.5	11	11	3.5	2	2
363.112.16.1	56 / 50	56	50	45	18	6	12	12	4	3	3

<i>Pol.č.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>x1 cm</i>	<i>x2 cm</i>	<i>x3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
363.115.16.1	56	56	56	45	18	6	12	12	4	2.5	2.5
364.109.16.1	60 / 40	63	40	45	19.5	6.5	13	13	4.5	4.5	4
364.112.16.1	60 / 50	63	50	45	19.5	6.5	13	13	5	3	3
364.115.16.1	60 / 56	63	56	45	19.5	6.5	13	13	4.5	2.5	2.5
364.120.16.1	60	63	63	45	19.5	6.5	13	13	4	2	2
365.109.16.1	70 / 40	75	40	45	21	7	14	14	6.5	5	6
365.112.16.1	70 / 50	75	50	45	21	7	14	14	6	3	4
365.115.16.1	70 / 56	75	56	45	21	7	14	14	5.5	2.5	3.5
365.120.16.1	70 / 60	75	63	45	21	7	14	14	4.5	2.5	3.5
365.125.16.1	70	75	75	45	21	7	14	14	4	2.5	2.5
366.109.16.1	90 / 40	90	40	45	24	8	16	16	7.5	5.5	6.5
366.112.16.1	90 / 50	90	50	45	24	8	16	16	8	4	5
366.115.16.1	90 / 56	90	56	45	24	8	16	16	7.5	3.5	4.5

<i>Pol.č.</i>	<i>DN</i>	<i>d, ø</i> mm	<i>d1, ø</i> mm	<i>arc</i> °	<i>H</i> cm	<i>x1</i> cm	<i>x2</i> cm	<i>x3</i> cm	<i>K1 max.</i> cm	<i>K2 max.</i> cm	<i>K3 max.</i> cm
366.120.16.1	90 / 60	90	63	45	24	8	16	16	7	3	4
366.125.16.1	90 / 70	90	75	45	24	8	16	16	6.5	3	3.5
366.130.16.1	90	90	90	45	24	8	16	16	5	2	2
367.109.16.1	100 / 40	110	40	45	27	9	18	18	9.5	6	7.5
367.112.16.1	100 / 50	110	50	45	27	9	18	18	9.5	5	5.5
367.115.16.1	100 / 56	110	56	45	27	9	18	18	9	4	4.5
367.120.16.1	100 / 60	110	63	45	27	9	18	18	8.5	3.5	4
367.125.16.1	100 / 70	110	75	45	27	9	18	18	7.5	3	3.5
367.130.16.1	100 / 90	110	90	45	27	9	18	18	6.5	2.5	3
367.135.16.1	100	110	110	45	27	9	18	18	5.5	2	2
368.120.16.1	125 / 60	125	63	45	30	10	20	20	10.5	4.5	6
368.125.16.1	125 / 70	125	75	45	30	10	20	20	9.5	4	5
368.130.16.1	125 / 90	125	90	45	30	10	20	20	8.5	3	3.5

<i>Pol.č.</i>	<i>DN</i>	<i>d, ø</i> mm	<i>d1, ø</i> mm	<i>arc</i> °	<i>H</i> cm	<i>x1</i> cm	<i>x2</i> cm	<i>x3</i> cm	<i>K1 max.</i> cm	<i>K2 max.</i> cm	<i>K3 max.</i> cm
368.135.16.1	125 / 100	125	110	45	30	10	20	20	7	2.5	2.5
368.139.16.1	125	125	125	45	30	10	20	20	6	2	2
369.125.16.1	150 / 70	160	75	45	37.5	12.5	25	25	13.5	6.5	7.5
369.130.16.1	150 / 90	160	90	45	37.5	12.5	25	25	12.5	5.5	6.5
369.135.16.1	150 / 100	160	110	45	37.5	12.5	25	25	11	4.5	5.5
369.139.16.1	150 / 125	160	125	45	37.5	12.5	25	25	10	4	5
369.145.16.1	150	160	160	45	37.5	12.5	25	25	7.5	2.5	2.5
370.125.16.1	200 / 70	200	75	45	54	18	36	36	8.5	10	2.5
370.135.16.1	200 / 100	200	110	45	54	18	36	36	7.5	10	0
370.139.16.1	200 / 125	200	125	45	54	18	36	36	5.5	9	0
370.145.16.1	200 / 150	200	160	45	54	18	36	36	4	5.5	0
370.146.16.1	200	200	200	45	54	18	36	36	0	0	0
371.135.16.1	250 / 100	250	110	45	66	22	44	44	14	10	7.5

<i>Pol.č.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>x1 cm</i>	<i>x2 cm</i>	<i>x3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
371.139.16.1	250 / 125	250	125	45	66	22	44	44	13	13	6.5
371.145.16.1	250 / 150	250	160	45	66	22	44	44	10.5	10	0
371.146.16.1	250 / 200	250	200	45	66	22	44	44	7.5	0	1.5
371.147.16.1	250	250	250	45	66	22	44	44	4	0	0
372.135.16.1	300 / 100	315	110	45	84	28	56	56	23	20	16
372.139.16.1	300 / 125	315	125	45	84	28	56	56	21.5	20	14.5
372.145.16.1	300 / 150	315	160	45	84	28	56	56	19.5	17.5	12.5
372.146.16.1	300 / 200	315	200	45	84	28	56	56	16.5	5	10
372.147.16.1	300 / 250	315	250	45	84	28	56	56	13	5.5	6.5
372.148.16.1	300	315	315	45	84	28	56	56	8.5	2	2