


# Odbočka kalhotová Geberit PE 2 x 30°



Obrázek s příkladem

## ÚČEL POUŽITÍ

- K odvodnění budov
- K odvodnění pozemků
- K vertikální montáži

## VLASTNOSTI

- Odolný vůči UV

## TECHNICKÉ ÚDAJE

Materiál

PE-HD

Pol.č.	DN	d, ø mm	d1, ø mm	arc °	X1 cm	X2 cm	K1 max. cm	K2 max. cm
361.459.16.1	50 / 40	50	40	30	5.5	11	4	5
361.462.16.1	50 / 50	50	50	30	5.5	11	3	4
363.462.16.1	56 / 50	56	50	30	6	12	4	5
363.465.16.1	56 / 56	56	56	30	1.8	5.3	0	0
364.462.16.1	60 / 50	63	50	30	6.5	13	5	6
364.465.16.1	60 / 56	63	56	30	6.5	13	4	6

<i>Pol.č.</i>	<i>DN</i>	<i>d, ø</i> <i>mm</i>	<i>d1, ø</i> <i>mm</i>	<i>arc</i> <i>°</i>	<i>X1</i> <i>cm</i>	<i>X2</i> <i>cm</i>	<i>K1 max.</i> <i>cm</i>	<i>K2 max.</i> <i>cm</i>
<b>365.465.16.1</b>	70 / 56	75	56	30	7	14	6	7
<b>365.470.16.1</b>	70 / 60	75	63	30	7	14	5	6
<b>367.480.16.1</b>	100 / 90	110	90	30	9	18	7	7
<b>367.481.16.1</b>	100 / 100	110	110	30	9	10.2	5	0